



## NC3MXX-50

3 pole male cable connector, 50<sup>th</sup> Anniversary Special Edition

To mark this milestone, we proudly present our 50th Anniversary Special Edition

Crafted with a unique dark grey conductive metal plating and the 50 years anniversary logo laser engraved, these connectors combine exceptional durability and elegance, while gold-plated contacts ensure superior performance and reliability.

### Features & Benefits

- |   |  |
|---|--|
| <ul style="list-style-type: none"><li>• conductive metal plating</li></ul>  | <ul style="list-style-type: none"><li>• gold plated contacts</li></ul>   |
| <ul style="list-style-type: none"><li>• Male connector with improved locking recess without "window", more stringent housing increases durability</li></ul> | <ul style="list-style-type: none"><li>• Boot with polyurethane gland gives high protection to cable bending stresses</li></ul> |
| <ul style="list-style-type: none"><li>• Internal thread on shell is well protected against any damage</li></ul>   | <ul style="list-style-type: none"><li>• Sleek and ergonomic design - valuable and handy</li></ul>                              |
| <ul style="list-style-type: none"><li>• Improved chuck type strain relief provides higher pull-out force and makes assembly easier and faster</li></ul>     | <ul style="list-style-type: none"><li>• Colored rings and boots available for coding or identification</li></ul>               |
| <ul style="list-style-type: none"><li>• Rugged zinc diecast shell, longlasting and dependable</li></ul>   |  |

## Technical Information

Product	
Title	NC3MXX-50
Product family	xlrCON
Connection type	cable connector
Gender	male

Electrical	
Capacity between contacts	$\leq 4 \text{ pF}$
Contact resistance	$\leq 3 \text{ m}\Omega$
Dielectric strength	1,5 kVdc
Insulation resistance	$> 10 \text{ G}\Omega$ (initial)
Rated current per contact	16 A
Rated voltage	50 Vac

Mechanical	
Cable O.D.	3.5 - 8.0 mm
Insertion force	$\leq 20 \text{ N}$
Withdrawal force	$\leq 20 \text{ N}$
Lifetime	min. 1000 mating cycles
Wiresize	max. 2.5mm <sup>2</sup>
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock

Material	
Boot	Polyurethan
Contact	Brass (CuZn39Pb3)
Contact plating	0.2 µm Au hard alloy over 2 µm Ni
Insert	Polyamide (PA66)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	50 years Special Edition plating CuNi
Strain relief	Polyacetal (POM)

Environmental	
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C