



## NC4MBV

4 pole male XLR receptacle, grounding: separate ground contact to mating connector shell and front panel, vertical PCB mount

Same as A series with exception of a metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC practice.

### Features & Benefits

- Smallest XLR receptacles, highest packing density
  - Metal mounting flange featuring continuous circumferential ground contact to chassis for best EMC and RF protection
- 
- Housing flammability UL 94 V-0

## Technical Information

| Product         |        |
|-----------------|--------|
| Title           | NC4MBV |
| Connection Type | XLR    |
| Gender          | male   |

| Electrical                   |                                                                                                     |
|------------------------------|-----------------------------------------------------------------------------------------------------|
| Capacitance between contacts | $\leq 7$ pF                                                                                         |
| Contact resistance           | $\leq 6$ m $\Omega$                                                                                 |
| Dielectric strength          | 1,5 kVdc                                                                                            |
| Insulation resistance        | $> 10$ G $\Omega$ (initial)                                                                         |
| Rated current per contact    | 6 A                                                                                                 |
| Rated voltage                | $< 50$ V                                                                                            |
| Grounding Options            | Separate ground contact connected to mating connector shell and front panel, no connection to Pin 1 |

| Mechanical         |                      |
|--------------------|----------------------|
| Insertion force    | ≤ 20 N               |
| Withdrawal force   | ≤ 20 N               |
| Lifetime           | > 1000 mating cycles |
| Wiresize           |                      |
| Wiring             | vertical PCB mount   |
| Locking device     | Latch lock           |
| Mounting direction | Rear mounting        |
| Chassis shape      | B                    |
| Mounting           | A-Screw              |

| Material        |                         |
|-----------------|-------------------------|
| Contacts        | Brass (CuZn35Pb2)       |
| Insert          | Polyamide (PA66)        |
| Locking element | Steel Ck67              |
| Ring            | Zinc diecast (ZnAl4Cu1) |
| Flange          | Metal                   |

| Environmental       |                           |
|---------------------|---------------------------|
| Flammability        | UL 94 V-0                 |
| Standard compliance | IEC 61076-2-103           |
| Protection class    | IP 40                     |
| Solderability       | Complies with IEC 68-2-20 |
| Temperature range   | -30 °C to +80 °C          |