



FIBERFOX EBC15 fiber optic cable terminated with expanded beam plug 4CH

- protection class: IP68 (up to 6m)
- core diameter: 50µm (multimode)
- operating temperatur: -40°C bis +70°C
- mating cycles: 5000

2x transparent shrink tube loose on both sides.
unshrunk for customized self-labeling before shrinking.

All FIBERFOX connectors meet the MIL-DTL-83526 standard.
FIBERFOX cable plugs are hermaphroditic, means no distinction in male in female. Two- and four-channel systems can be mixed.
(Attention: in this case only chanel A1 and B1 works)

Description	Stock-Code	Length	Weight
NKO4M3-FX-0-005 airspool	1027412	5 m	0,36 kg
NKO4M3-FX-0-010 airspool	1027413	10 m	0,50 kg
NKO4M3-FX-0-020 airspool	1027414	20 m	0,79 kg
NKO4M3-FX-0-050 airspool	1027415	50 m	1,66 kg
NKO4M3-FX-0-100 airspool	1027416	100 m	3,11 kg
NKO4M3-FX-0-150 airspool	1027417	150 m	4,56 kg
NKO4M3-FX-2-050 cable reel	1027418	50 m	3,26 kg
NKO4M3-FX-2-100 cable reel	1027419	100m	4,71 kg
NKO4M3-FX-2-150 cable reel	1027420	150 m	6,16 kg

No.	Part	Qty.
1	Expanded beam plug 4ch MM cable 6mm plug	2
2	TD-04G50-OM3-MIL	1
3	Shrink Tube Ø 6,4 -> 3,2 unshrunked	2

Sheet Number 1/1	Projection 	Scale 1:2	Format A4	Tolerancing ISO 2768- m	
g	cm ²	cm ³	Created	HeBo	10.06.2021
Material			Modified		
Material addition			Approved	DiRo	10.06.2021
Description NK04M3-FX FIBERFOX EBC15 cable 4CH MM OM3			ECN Number		
NEUTRIK			Status	FOR FINAL	
3D Model ID			Document ID	Revision 01	